

Delivering Engineered Packaging Solutions

◆ COMPETITIVE ◆ QUALITY ◆ EXPERIENCED ◆ RELIABLE ◆ INNOVATIVE ◆ INTEGRATED

PL105 LIDDING FILM - *PEELABLE & HIGH BARRIER*

TRANSPARENT PEELABLE & HIGH BARRIER

PL105 Perfect Application

- Peelable on PP, PS and PVC
- Excellent for fresh or frozen entrees and where tamper evidence is needed.
- Suitable to use in microwave and conventional oven
- Available in 138 gauge to 295 gauge.

Solvent Free



PL105 The Ideal Film

- Transparent High Barrier Film
- High Gas-Barrier version available
- Also available in White Opaque & Metalized
- Allows printing in common techniques

Property		Unit	Value			
Total Thickness		gauge	137	177	216	295
Yield		Sq. m /lb.	18.6	14.79	12.1	9.09
Roll Width		In.	3.75 to 47			
Standard Roll Length		Ft	1625, 3250			
Roll Outer Diameter		In.	8 to 13.75			
Roll Inner Diameter		In.	Standard 3" core			
Roll Weight		Lbs.	11 to 440			
High Barrier			Optional			
Printable			Yes			
Anti-Fog			Optional			
Permeability		g	Standard		High Barrier	
	H ₂ O	$\frac{\text{ml}}{\text{m}^2 \times \text{d}}$	5		4	
	CO ₂	ml	450		23	
	O ₂	$\text{m}^2 \times \text{d} \times \text{bar}$	165		8	

¹ Test Conditions 25° C, 50% RH, 1 Bar

PL105 Films, all of the raw material used in the making of the films are approved for food contact in accordance to ECC and/or the FDA regulations.

